

I. 24-HOUR EMERGENCY CONTACT INFORMATION

CHEM-TEL United States..... 800-255-3924
 International 813-248-0585

II. HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Component Identification	CASRN	OSHA PEL	ACGIH TLV	% (by weight)
Amine Mixture	Proprietary	None	Established	100

(1) These materials are substantially incorporated into the mixture and exposure via inhalation is not likely to occur.

Product Description.....**AMINE**

III. PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point > 482°F (250°C)
 Melting Point Not Determined
 Vapor Pressure < 1 mmHg @ 68°F (20°C)
 Vapor Density (Air = 1)..... 7.6
 Specific Gravity (Water = 1) ~ 1
 Evaporation Rate (butyl acetate = 1) Not Determined
 pH..... Not Determined, Corrosive
 Appearance and Odor..... Liquid, Amine Odor
 Odor Threshold Not Determined

IV. FIRE and EXPLOSION HAZARDS

Flash Point ~ 261°F (127°C), Pensky-Martens Closed Cup
 Autoignition Temperature..... Not Determined
 LEL / UEL..... Not Determined
 Extinguishing Media Dry Chemical, CO₂, Water Fog, Alcohol Foam
 NFPA Ratings Health (3) – Flammability (1) – Reactivity (1)

Special Firefighting Procedures: Do not direct a solid stream of water into hot burning polls, this may cause frothing and increase fire intensity. Use self-contained breathing apparatus and protective clothing.

Fire and Explosion Hazards: During a fire, oxides of nitrogen may be produced.

V. REACTIVITY DATA

Stability..... Stable
 Hazardous Polymerization Will Not Occur
 Conditions to Avoid Do not mix with nitrates or other nitrosating agents
 Incompatibilities..... Oxidizing Materials
 Hazardous Decomposition Products NO_x, CO, and CO₂

VI. HEALTH HAZARD DATA

Route(s) of Entry: Inhalation..... Yes
 Skin Yes
 Ingestion..... Not Expected

Acute (Short-Term) Health Effects: This material is corrosive and irritating to the eyes, throat, and skin. Eye exposure may cause severe irritation with corneal injury that may result in permanent impairment, even blindness. Short-term skin exposure may cause severe burns and/or allergic skin reaction. Prolonged or widespread skin

contact could result in the material being absorbed in harmful amounts. Inhalation of vapors may be irritating to the nose, throat, and chest causing runny nose and stuffiness, cough, and possibly difficulty breathing.

Chronic (Long-Term) Health Effects: Repeated or prolonged contact with the skin may cause dermatitis and skin sensitization.

Carcinogenicity: None of the chemicals in this product are classified as known of potential human carcinogens by the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC), or OSHA.

Signs and Symptoms of Exposure: Signs and symptoms following exposure may include irritation and burning sensation to eyes, skin, and respiratory tract (if inhaled).

Medical Conditions Generally Aggravated by Exposure: Excessive exposure may aggravate preexisting asthma and dermatitis.

Emergency and First Aid Procedures:

Inhalation: Remove to fresh air if exposure symptoms develop and seek medical attention.

Skin Contact: Gently wash all affected skin areas thoroughly with water soap and water while removing contaminated clothing. If irritation persists or burning sensation is evident, seek medical attention.

Eye Contact: Flush eyes with water for 20 to 30 minutes. Obtain prompt medical attention, preferably from an ophthalmologist.

Ingestion: Not expected under normal use conditions. However, if ingestion does occur, do not induce vomiting. Give large amounts of water or milk and seek medical attention.

HMIS Ratings..... Health (3) – Flammability (1) – Reactivity (1)

VII. PRECAUTIONS FOR SAFE HANDLING and USE

Steps to be Taken in Case Material is Released or Spill: Due to the relatively small end-use container sizes, significant spills are unlikely. However, if a spill does occur, collect and place into a suitable container for disposal. Do not allow spilled materials to enter storm sewers, sanitary sewers, or impact ground water.

Waste Disposal Method: Disposal must be in accordance with applicable laws.

Precautions to be Taken in Handling and Storage: Copper and copper alloys should not be used for storage as the product may quickly corrode them.

VIII. CONTROL MEASURES

Respiratory Protection: None typically required for normal use. Self-contained breathing apparatus may be needed if product is used in a confined or poorly ventilated area.

Ventilation: A system of local and/or general exhaust is recommended.

Hand Protection: Gloves impervious to this material should be worn.

Eye Protection: ANSI-approved safety glasses with side shields or chemical goggles.

Other: Such clothing as to minimize or eliminate skin contact.

IX. REGULATORY INFORMATION (Not meant to be all-inclusive)

Hazardous Materials Transportation Act (HMTA)

This material should be classified as follows:

Proper Shipping Name..... Amines, Liquid, Corrosive, n.o.s., Mixture
(3,3'-(Oxybis (2,1-Ethanedioxy)) Bis-1-Propanamine)
Hazard Class..... 8
Identification Number UN2735

Packaging Group II
Label Required.....Corrosive

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

This produce contains the following CERCLA Section 102(a) hazardous substance(s) as listed in 40 CFR 302.4:

Identity	CASRN	% (by weight)	Reportable Quantity (RQ)
None			

Superfund Amendment and Reauthorization Act (SARA)

This product contains the following SARA Title III Section 302 extremely hazardous substance(s) as listed in 40 CFR Part 355:

Identify	CASRN	% (by weight)
None		

SARA Title III Section 311/312 hazardous categorization:

This product has been reviewed according to the EPA hazard categories promulgated under SARA Tile III Section 311 and 312 and is considered to meet the following hazard categories:

- An immediate (acute) health hazard
- A delayed (chronic) health hazard

This product contains the following SARA Title III Section 313 toxic substance(s) as listed in 40 CFR Part 372:

Identify	CASRN	% (by weight)
None		

Toxic Substances Control Act (TSCA)

All ingredients are on the TSCA inventory or are not required to be on the inventory.

CATALYST / HARDENER INDEX

The material described in this MSDS is intended for use with the following:

DS 2000 SERIES PART A

Review literature supplied with product or contact Smith Fibercast for proper mixing ratios.

The information contained herein is believed to be accurate. However, we cannot assume any liability whatsoever for the accuracy or completeness of the information provided. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

SMITH FIBERCAST

2700 West 65th Street, Little Rock, Arkansas 72209 • 501-568-4010 • FAX 501-568-4465
25 South Main Street, Sand Springs, Oklahoma 74063 • 918-245-6651 • FAX 918-245-7566
www.smithfibercast.com